



Test Report: IRM-45-48

45W AC-DC PCB-Mount Green Power Module

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE(Max)	V1: 300mVp-p	I/P:230VAC O/P:FULL LOAD Ta:25 °C	V1: 78.4 mVp-p	P
2	OUTPUT VOLTAGE(Max) TOLERANCE	V1: -2.5%~ 2.5%	I/P: 85VAC /305VAC O/P:FULL/ MIN. LOAD Ta:25 °C	V1: -0.037 %~ 0.037%	P
3	LINE REGULATION (Max)	V1: -0.5%~ 0.5%	I/P: 100VAC~ 305VAC O/P:FULL LOAD Ta:25 °C	V1: -0.037 %~ 0%	P
4	LOAD REGULATION(Max)	V1: -0.5%~ 0.5%	I/P: 230VAC O/P:FULL ~MIN LOAD Ta:25 °C	V1: 0 %~ 0.037%	P
5	SET UP TIME(Max)	230VAC/1000ms 115VAC/2000ms	I/P 230 VAC I/P 115 VAC O/P FULL LOAD Ta 25 °C	230VAC/ 415.234ms 115VAC/ 492.683ms	P
6	RISE TIME (Max)	230VAC/30ms 115VAC/30ms	I/P 230 VAC I/P 115 VAC O/P FULL LOAD Ta 25 °C	230VAC/ 16.753ms 115VAC/ 18.119ms	P
7	HOLD UP TIME(Typ)	230VAC/50ms 115VAC/12ms	I/P 230 VAC I/P 115 VAC O/P FULL LOAD Ta 25 °C	230VAC/ 76.742ms 115VAC/ 16.253ms	P
8	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230VAC O/P:FULL LOAD Ta:25 °C	< ±5%	P
9	DYNAMIC LOAD	V1: 4800mVp-p	I/P: 230VAC O/P(1)FULL /Min LOAD 90%DUTY / 1KHZ (2) (1)FULL /Min LOAD 90%DUTY / 3KHZ (3)FULL /Min LOAD 90%DUTY / 5KHZ (4)FULL /Min LOAD 50%DUTY / 120HZ Ta:25 °C	352mVp-p 212 mVp-p 162mVp-p 416mVp-p	P
10	TRANSIENT RECOVERY TIME	V1: 4800mVp-p <500us	I/P: 230VAC O/P:40% LOAD CHANGE 50%DUTY/120HZ 1.25A/us	217 mVp-p 0 us	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	85VAC~305VAC	I/P:TESTING O/P:FULL LOAD Ta:25 ~	75.8V~305V	P
			I/P: (1)LOW-LINE-3V=97 V HIGH-LINE+15%=300 V O/P:FULL/MIN LOAD ON: 30 Sec OFF: 30 Sec 10MIN (2)230Vac ON: 0.5 Sec OFF: 0.5 Sec 20MIN (3)230Vac ON:3Sec OFF:3Sec 12HOURS (POWER ON/OFF NO DAMAGE)	TEST:OK	
2	INPUT FREQUENCY RANGE	47HZ ~440 HZ NO DAMAGE	I/P:85 VAC ~305 VAC O/P:FULL~MIN LOAD Ta:25 ~	TEST: OK	P
3	EFFICIENCY(TYP)	90.5%	I/P:230 VAC O/P:FULL LOAD Ta:25 ~	91.81%	P
4	INPUT CURRENT (Typ)	230V/ 0.9A 115V/ 1.5A 277V/ 0.75A	I/P 230 VAC/115VAC/277VAC O/P FULL LOAD Ta 25 ~	I=0.377A/ 230VAC I=0.731A/ 115VAC I=0.315A/ 277VAC	P
5	INRUSH CURRENT(Typ)	230V/60A 115V/30A COLD START	I/P 230 VAC I/P 115 VAC O/P FULL LOAD Ta 25 ~	I=46.687A/ 230VAC I=27.2A/ 115VAC	P
6	LEAKAGE CURRENT	< 0.25 mA / 277 VAC	I/P 277 VAC O/P Min LOAD Ta 25 ~	L-FG 0.011 mA N-FG 0.011 mA	P
7	NO LOAD CONSUMPTION	< 0.15 W	I/P 115VAC I/P 230VAC O/P NO LOAD Ta 25 ~	< 0.0476 W < 0.0757 W	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	115%~160%	I/P: 230VAC I/P: 115VAC O/P:TESTING Ta:25 ~	147.87%/ 230VAC 142.55%/115VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH:50.4V~64.8V	I/P: 230VAC I/P: 115VAC O/P:MIN LOAD Ta:25 ~	51.8V Other shut off o/p voltage,clamping by zener diode	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 305VAC O/P: FULL LOAD Ta:25 ~	NO DAMAGE Hiccup Mode	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	PWM Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated 13A/650V	I/P:High-Line =305V AC ON/OFF VDS: O/P: (1)Full Load (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/1KHz (4)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (5)Dynamic Load Full Load/ Min. Load 90%Duty/5KHz (6)Dynamic Load 100% Load/ Min. Load 50%Duty/120Hz (7)0% 400% Load. I/P:Low-Line -3V = 97V O/P: (1)Full Load (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/1KHz (4)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (5)Dynamic Load Full Load/ Min. Load 90%Duty/5KHz (6)Dynamic Load 100% Load/ Min. Load 50%Duty/120Hz (7)0% 400% Load. Ta:25	(1)578V (2) 636V (3)596V (4)586V (5)578V (6)592V (7) 596V (1)338V/A (2)229V/A (3)354V/A (4)342V/A (5)340V/A (6)360V/A (7)378V/A	P
2	Diode Peak Voltage	D100 Rated 20A/300V	I/P:High-Line =305V AC ON/OFF O/P: (1)Full Load (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/1KHz (4)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (5)Dynamic Load Full Load/ Min. Load 90%Duty/5KHz (6)Dynamic Load 100% Load/ Min. Load 50%Duty/120Hz (7)0% 400% Load. (8).NO LOAD Ta:25	D100: (1)186V (2)215V (3)183V (4)182V (5)185V (6)186V (7)187V (8)183V	P
3	Input Capacitor Voltage	C5 Rated: 105 VZ Series	I/P:High-Line =305V O/P: (1)Full Load input on/off (2) Min load input on /Off (3)Full Load /Min load Change Ta:25	(1)362V (2)363V (3)364V	P
4	Control IC Voltage Test	PWM IC U1 Rated :10V~27V	I/P:High-Line =305V AC ON/OFF O/P:(1)FULL LOAD (2) Output Short (3)O.L.P Ta:25	(1) 17.3V (2) 17.3V (3) 17.3V	P

5	Clamp Diode Peak Voltage	D 5 Rated RD 2A/800V GP20K	I/P:High-Line =305V AC ON/OFF O/P (1) Dynamic Load 90%Duty/1KHz (2)Full load continue Ta 25 ~	(1) 522 V (2) 518 V	P
---	--------------------------	-------------------------------	--	------------------------	---

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 4KVAC/min	I/P-O/P: 4.4 KVAC/min Ta:25 ~	I/P-O/P:1.94mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P: 500 VDC Ta:25 ~	I/P-O/P: 9999MΩ NO DAMAGE	P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	BS EN/EN61000-3-2 CLASS A	I/P 230 VAC/50HZ O/P FULL LOAD Ta 25°C	PASS	P
2	CONDUCTION	BS EN/EN55032(CISPR32) CNS13438 CLASS B	I/P 230 VAC (50HZ) O/P FULL/50% LOAD Ta 25°C	PASS Test by certified Lab	P
3	RADIATION	BS EN/EN55032(CISPR32) CNS13438 CLASS B	I/P 230 VAC (50HZ) O/P FULL LOAD Ta 25°C	PASS Test by certified Lab	P
4	E.S.D	BS EN/EN61000-4-2 AIR 8KV / Contact 4KV	I/P 230 VAC/50HZ O/P FULL LOAD Ta 25 ~	CRITERIA A	P
5	E.F.T	BS EN/EN61000-4-4 INPUT 2KV	I/P 230 VAC/50HZ O/P FULL LOAD Ta 25 ~	CRITERIA A	P
6	SURGE	BS EN/EN61000-4-5 L-N 2KV	I/P 230 VAC/50HZ O/P FULL LOAD Ta 25 ~	CRITERIA A	P
7	Test by certified Lab Test Report Prepare				

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																								
1	TEMPERATURE RISE TEST	MODEL IRM-45-24 1. ROOM AMBIENT BURN-IN 1HRS I/P 230VAC O/P FULL LOAD Ta= 21.4 ~ 2. HIGH AMBIENT BURN-IN 1HRS I/P 230VAC O/P FULL LOAD Ta=53.1 ~	<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta=21.4 ~</th> <th>HIGH AMBIENT Ta=53.1 ~</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>46.7°C</td><td>76.3°C</td></tr> <tr><td>2</td><td>BD1</td><td>46.7°C</td><td>78.3°C</td></tr> <tr><td>3</td><td>C5</td><td>48.4°C</td><td>79.1°C</td></tr> <tr><td>4</td><td>D5</td><td>51.0°C</td><td>82.8°C</td></tr> <tr><td>5</td><td>C40</td><td>51.5°C</td><td>82.4°C</td></tr> <tr><td>6</td><td>Q1</td><td>54.7°C</td><td>87.5°C</td></tr> <tr><td>7</td><td>T1</td><td>55.8°C</td><td>86.2°C</td></tr> <tr><td>8</td><td>C105</td><td>50.8°C</td><td>82.6°C</td></tr> <tr><td>9</td><td>D100</td><td>63.8°C</td><td>93.9°C</td></tr> <tr><td>10</td><td>D43</td><td>48.5°C</td><td>80.0°C</td></tr> <tr><td>11</td><td>U1</td><td>49.0°C</td><td>79.8°C</td></tr> <tr><td>12</td><td>D40</td><td>52.6°C</td><td>83.3°C</td></tr> <tr><td>13</td><td>CASE</td><td>47.3°C</td><td>78.6°C</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta=21.4 ~	HIGH AMBIENT Ta=53.1 ~	1	LF1	46.7°C	76.3°C	2	BD1	46.7°C	78.3°C	3	C5	48.4°C	79.1°C	4	D5	51.0°C	82.8°C	5	C40	51.5°C	82.4°C	6	Q1	54.7°C	87.5°C	7	T1	55.8°C	86.2°C	8	C105	50.8°C	82.6°C	9	D100	63.8°C	93.9°C	10	D43	48.5°C	80.0°C	11	U1	49.0°C	79.8°C	12	D40	52.6°C	83.3°C	13	CASE	47.3°C	78.6°C		P
NO	Position	ROOM AMBIENT Ta=21.4 ~	HIGH AMBIENT Ta=53.1 ~																																																										
1	LF1	46.7°C	76.3°C																																																										
2	BD1	46.7°C	78.3°C																																																										
3	C5	48.4°C	79.1°C																																																										
4	D5	51.0°C	82.8°C																																																										
5	C40	51.5°C	82.4°C																																																										
6	Q1	54.7°C	87.5°C																																																										
7	T1	55.8°C	86.2°C																																																										
8	C105	50.8°C	82.6°C																																																										
9	D100	63.8°C	93.9°C																																																										
10	D43	48.5°C	80.0°C																																																										
11	U1	49.0°C	79.8°C																																																										
12	D40	52.6°C	83.3°C																																																										
13	CASE	47.3°C	78.6°C																																																										
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P 230 VAC O/P 144 LOAD Ta 25 ~	TEST OK	P																																																								
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P 305VAC/100VAC O/P 100 LOAD Ta=-30 ~	TEST OK	P																																																								
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 ~ NO DAMAGE	I/P 305 VAC O/P FULL LOAD Ta=50 ~ HUMIDITY= 95 %R.H	TEST OK	P																																																								
5	TEMPERATURE COEFFICIENT	± 0.03%/ -(0-50 ~)	I/P 230 VAC O/P FULL LOAD	± 0.003%/ -(0-50 ~)	P																																																								
6	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -40°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P																																																								
7	THERMAL SHOCK TEST	1. Thermal shock Temperature : -30°C~ +70°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec		OK	P																																																								



8	VIBRATION TEST	1 Carton & 1 Set (1) Waveform Sine Wave (2) Frequency 10~500Hz (3) Sweep Time 12min/sweep cycle (4) Acceleration 2G (Blank) /5G (ST) (5) Test Time 60min in each axis (X.Y.Z) (6) Ta 25 ~	TEST OK	P
9	CAPACITOR LIFE CYCLE	SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P 230VAC O/P FULL LOAD Ta=25 ~ LIFE TIME (2) I/P 230VAC O/P FULL LOAD Ta=50 ~ LIFE TIME (3) I/P 230VAC O/P 75% LOAD Ta=50 ~ LIFE TIME (4) I/P 230VAC O/P 50% LOAD Ta=50 ~ LIFE TIME	(1) 410328HRS (2) 72078HRS (3) 79950HRS (4) 130749HRS	P
10	MTBF	MIL-HDBK-217F TOTAL FAILURE RATE 1212KHRS		P
11	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure (Expected Life): Above 30,000 hours @ TA 50 ~		P

TEST RESULT	TESTER	APPROVAL
PASS	Frank	Wangdz

2007/3/20 A50-S014